



單位:MM

Standard 標準	Size 規格	KG/PC 單重	D 外徑	d 內徑	T 厚度	C 中心距	n 孔數	H 孔徑	F 槽外徑	e 壁厚	f 槽深	K 邊高	r	R
ASA 150LB	1" — 25A	0.68	108.0	40	14	79.0	4	15.9	62	3	5.0	3.0	1.5	10
ASA 150LB	1.1/4" — 32A	0.77	118.0	52	14	89.0	4	15.9	70	3	5.0	3.0	1.5	10
ASA 150LB	1.1/2" — 40A	0.96	127.0	52	14	98.0	4	15.9	70	3	5.0	3.0	1.5	10
ASA 150LB	2" — 50A	1.58	152.4	63	16	120.7	4	19	88	3	6.0	3.5	1.5	10
ASA 150LB	2.1/2" — 65A	2.29	177.8	83	18	139.7	4	19	107	3	6.0	4.0	1.5	14
ASA 150LB	3" — 80A	2.54	190.5	92	18	152.4	4	19	119	3	7.0	4.0	2.0	14
ASA 150LB	4" — 100A	3.20	228.6	120	18	190.5	8	19	152	4	8.5	4.5	2.0	15
ASA 150LB	5" — 125A	3.98	254.0	146	20	215.9	8	22	183	4	8.5	4.5	2.0	15
ASA 150LB	6" — 150A	4.88	279.4	171	22	241.3	8	22	212	4	9.0	5.5	3.0	16
ASA 150LB	8" — 200A	7.36	342.9	220	22	298.5	8	22	264	6	9.0	5.5	3.0	16
ASA 150LB	10" — 250A	10.33	406.4	270	24	362.0	12	25	324	8	10.0	6.5	4.0	16
ASA 150LB	12" — 300A	15.54	482.6	322	24	431.8	12	25	373	8	10.0	6.5	4.0	16
ASA 150LB	14" A — 350A	18.63	533.4	375	26	476.3	12	28	422	8	11.0	7.0	4.0	17
ASA 150LB	16" A — 400A	24.86	596.9	414	28	539.8	16	28	475	8	13.0	7.0	5.0	18
ASA 150LB	18" A — 450A	25.67	635.0	464	30	577.9	16	32	525	10	15.0	8.0	5.0	19
ASA 150LB	20" A — 500A	30.91	698.5	513	30	635.0	20	32	576	10	15.0	8.0	5.0	19
ASA 150LB	22" — 550A	28.26	749.3	588	30	692.1	20	35	645	10	15.0	8.0	5.0	19
ASA 150LB	24" — 600A	35.86	813.0	632	30	749.3	20	35	692	10	15.0	8.0	5.0	19
ASA 150LB	26" — 650A	39.72	870.0	690	32	806.5	24	35	755	12	16.0	7.0	5.0	19
ASA 150LB	28" — 700A	47.24	927.1	730	32	863.6	28	35	795	12	16.0	7.0	5.0	19
ASA 150LB	30" A — 750A	52.40	984.3	780	32	914.4	28	35	850	12	16.0	7.0	5.0	19
ASA 150LB	14" B — 350A b	17.81	533.4	375	26	476.3	12	28	438	8	11.0	7.0	4.0	17
ASA 150LB	16" B — 400A b	24.01	596.9	414	28	539.8	16	28	488	8	13.0	7.0	5.0	18
ASA 150LB	18" B — 450A b	24.59	635.0	464	30	577.9	16	32	538	10	15.0	8.0	5.0	19
ASA 150LB	20" B — 500A b	29.73	698.5	513	30	635.0	20	32	589	10	15.0	8.0	5.0	19
ASA 150LB	30" B — 750A b	45.87	984.3	800	32	914.4	28	35	872	12	16.0	7.0	5.0	19

外 徑 (D) +1.0MM-0MM

孔 徑 (H) ±0.3MM

內 徑 (d) +0.5MM-0MM

旋 距: ±0.5MM

厚 度 (T) +1.0MM-0MM

同心度: ±0.3MM

中 心 距 (C) ±0.5MM

平行度: ±0.5MM



蚨鑫国际有限公司

FU XIN INTERNATIONAL CO., LIMITED

ASA 150LB

畫 圖

製 表

審 核

Tyler Zhao

標 準 Rubber joint Flange

材 質 Carbon Steel: Q235B

日 期 04/Sep/2021