



單位:MM

Standard 標準	Size 規格	KG/PC 單重	D 外徑	d 內徑	T 厚度	C 中心距	n 孔數	H 孔徑	F 槽外徑	e 壁厚	f 槽深	K 邊高	r	R
BS10 TABLE D	1" — 25A	0.88	114.3	40	15	82.6	4	16	62	3	5.0	3.0	1.5	10
BS10 TABLE D	1.1/4" — 32A	0.91	120.7	52	15	87.3	4	16	70	3	5.0	3.0	1.5	10
BS10 TABLE D	1.1/2" — 40A	1.21	133.4	52	15	98.4	4	16	70	3	5.0	3.0	1.5	10
BS10 TABLE D	2" — 50A	1.60	152.0	63	16	114.3	4	18	88	3	6.0	3.5	1.5	10
BS10 TABLE D	2.1/2" — 65A	1.65	165.0	83	16	127.0	4	18	106	3	6.0	4.0	1.5	14
BS10 TABLE D	3" — 80A	2.33	184.0	92	18	146.0	4	19	119	3	7.0	4.0	2	14
BS10 TABLE D	4" — 100A	2.86	216.0	120	18	177.8	4	19	152	4	8.5	4.5	2	15
BS10 TABLE D	5" — 125A	4.21	254.0	146	20	210.0	8	19	183	4	8.5	4.5	2	15
BS10 TABLE D	6" — 150A	5.17	279.0	171	22	235.0	8	19	212	4	9.0	5.5	3	16
BS10 TABLE D	8" — 200A	7.13	337.0	220	22	292.0	8	19	264	6	9.0	5.5	3	16
BS10 TABLE D	10" — 250A	11.03	406.0	270	24	355.6	8	22	324	8	10.0	6.5	4	16
BS10 TABLE D	12" — 300A	12.48	457.0	322	24	406.4	12	22	373	8	10.0	6.5	4	16
BS10 TABLE D	14" — 350A	18.18	527.0	375	26	470.0	12	25	422	8	11.0	7.0	4	17
BS10 TABLE D	16" — 400A	22.30	578.0	414	28	520.7	12	25	475	8	13.0	7.0	5	18
BS10 TABLE D	18" — 450A	29.23	641.0	464	30	584.2	12	25	525	10	15.0	8.0	5	19
BS10 TABLE D	20" — 500A	35.11	705.0	513	30	641.4	16	25	576	10	15.0	8.0	5	19
BS10 TABLE D	22" — 550A	34.68	762.0	588	30	698.5	16	28	645	10	15.0	8.0	5	19
BS10 TABLE D	24" — 600A	42.54	825.5	632	30	755.7	16	28	692	10	15.0	8.0	5	19

外徑 (D) +1.0MM-0MM

孔徑 (H) ±0.3MM

內徑 (d) +0.5MM-0MM

旋距: ±0.5MM

厚度 (T) +1.0MM-0MM

同心度: ±0.3MM

中心距 (C) ±0.5MM

平行度: ±0.5MM



蚨鑫国际有限公司

FU XIN INTERNATIONAL CO., LIMITED

BS10 TABLE D

畫圖

製表

審核

Tyler Zhao

標準

材質

日期

Rubber joint Flange

Carbon Steel: Q235B

04/Sep/2021