



標準 Standard	規格 Size	單重 KG/PC	外径 D	內徑 B	厚度 T	槽內徑 B1	槽深 t	中心距 K	孔數 J	孔徑 H	R
DIN PN10 JM	1" — 25A	0.91	115	46	16	68	7	85	4	14	3
DIN PN10 JM	1.1/4" — 32A	1.43	140	54	16	70	7	100	4	18	3
DIN PN10 JM	1.1/2" — 40A	1.63	150	60	16	78	7	110	4	18	3
DIN PN10 JM	2" — 50A	2.20	165	71	18	88	7	125	4	18	3
DIN PN10 JM	2.1/2" — 65A	2.65	185	85	18	109	7	145	4	18	3
DIN PN10 JM	3" — 80A	3.25	200	97	20	119	7	160	8	18	3
DIN PN10 JM	4" — 100A	3.44	220	125	20	149	7	180	8	18	3
DIN PN10 JM	5" — 125A	4.52	250	155	22	179	7	210	8	18	3
DIN PN10 JM	6" — 150A	5.43	285	180	22	208	10	240	8	22	3
DIN PN10 JM	8" — 200A	7.92	340	231	24	255	10	295	8	22	3
DIN PN10 JM	10" — 250A	10.32	395	282	26	310	10	350	12	22	3
DIN PN10 JM	12" — 300A	11.31	445	333	26	373	10	400	12	22	5
DIN PN10 JM	14" — 350A	14.68	505	390	28	425	10	460	16	22	5
DIN PN10 JM	16" — 400A	19.72	565	437	30	473	10	515	16	26	5
DIN PN10 JM	18" — 450A	20.43	615	492	30	528	10	565	20	26	5
DIN PN10 JM	20" — 500A	23.41	670	540	30	586	10	620	20	26	5
DIN PN10 JM	24" — 600A	28.55	780	640	30	690	12	725	20	30	5
DIN PN10 JM	32" — 800A	49.45	1015	845	32	897	14	950	24	33	5
DIN PN10 JM	76" — 1900A	227.00	2220	1980	50	2060	25	2125	48	48	5

※ 法蘭各部尺寸公差

外 徑 (D) +1.0MM-0MM	孔 徑 (H) ±0.3MM
內 徑 (d) +0.5MM-0MM	旋 距: ±0.5MM
厚 度 (T) +1.0MM-0MM	同心度: ±0.3MM
中 心 距 (C) ±0.5MM	平行度: ±0.5MM

		蚨鑫国际有限公司 FU XIN INTERNATIONAL CO., LIMITED	
		DIN PN10 JM	
畫 圖		標 準	Rubber joint Flange
製 表		材 質	Carbon Steel: Q235B
審 核		日 期	04/Sep/2021