



單位:MM

Standard	Size	KG/PC	D	d	T	C	n	H	F	e	f	K	r	R
標 準	規 格	單 重	外徑	內徑	厚度	中心距	孔數	孔徑	槽外徑	壁厚	槽深	邊高		
JPI150LB	1" — 25A	0.72	108.0	40	14.5	79.0	4	16	62	3	5.0	3.0	1.5	10
JPI150LB	1.1/4" — 32A	0.92	118.0	52	16.0	89.0	4	16	70	3	5.0	3.0	1.5	10
JPI150LB	1.1/2" — 40A	1.25	127.0	52	17.5	98.0	4	16	70	3	5.0	3.0	1.5	10
JPI150LB	2" — 50A	1.98	152.4	63	19.5	120.7	4	19	88	3	6.0	3.5	1.5	10
JPI150LB	2.1/2" — 65A	2.99	177.8	83	22.5	139.7	4	19	107	3	6.0	4.0	1.5	14
JPI150LB	3" — 80A	3.58	190.5	92	24.0	152.4	4	19	119	3	7.0	4.0	2.0	14
JPI150LB	4" — 100A	4.62	228.6	120	24.0	190.5	8	19	152	4	8.5	4.5	2.0	15
JPI150LB	5" — 125A	5.06	254.0	146	24.0	215.9	8	22	183	4	8.5	4.5	2.0	15
JPI150LB	6" — 150A	6.04	279.4	171	25.5	241.3	8	22	212	4	9.0	5.5	3.0	16
JPI150LB	8" — 200A	10.37	342.9	220	29.0	298.5	8	22	264	6	9.0	5.5	3.0	16
JPI150LB	10" — 250A	13.83	406.4	270	30.5	362.0	12	26	324	8	10.0	6.5	4.0	16
JPI150LB	12" — 300A	21.68	482.6	322	32.0	431.8	12	26	373	8	10.0	6.5	4.0	16
JPI150LB	14" — 350A	26.28	533.4	375	35.0	476.3	12	29	422	8	11.0	7.0	4.0	17
JPI150LB	16" — 400A	34.63	596.9	414	37.0	539.8	16	29	475	8	13.0	7.0	5.0	18
JPI150LB	18" — 450A	36.76	635.0	464	40.0	577.9	16	32	525	10	15.0	8.0	5.0	19
JPI150LB	20" — 500A	47.86	698.5	513	43.0	635.0	20	32	576	10	15.0	8.0	5.0	19

外 徑 (D) +1.0MM-0MM

孔 徑 (H) ± 0.3 MM

內 徑 (d) +0.5MM-0MM

旋 距: ± 0.5 MM

厚 度 (T) +1.0MM-0MM

同心度: ± 0.3 MM

中 心 距 (C) ± 0.5 MM

平行度: ± 0.5 MM



蚨鑫国际有限公司

FU XIN INTERNATIONAL CO., LIMITED

JPI150LB

畫 圖

製 表

審 核

Tyler Chao

標 準

材 質

日 期

Rubber joint Flange

Carbon Steel: Q235B

04/Sep/2021